REMARKS

This Preliminary Amendment cancels without prejudice original claims 1 to 10 in the underlying PCT Application No. PCT/DE03/01998. This Preliminary Amendment adds new claims 11 to 20. The new claims are believed to conform to the U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.121(b)(3), the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. § 1.121(b)(3)(iii) and § 1.125(b)(2), a Marked Up Version Of The Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. In the Marked Up Version, underlining indicates added text and strikeouts indicate deleted text. Approval and entry of the Substitute Specification (including Abstract) is respectfully requested.

The underlying PCT Application No. PCT/DE03/01998 includes an International Search Report, dated October 17, 2003. The Search Report includes a list of documents that were uncovered in the underlying PCT Application. An English translation of the Search Report accompanies this Preliminary Amendment. The underlying PCT Application No. PCT/DE03/01998 also includes an International Preliminary Examination Report, dated September 17, 2004. An English translation of the International Preliminary Examination Report (including a translation of the annexes to the Report, i.e., page 1 of the Specification and claims 1 to 10) accompanies this Preliminary Amendment.

Applicant asserts that the subject matter of the present application is new, nonobvious, and useful. Prompt consideration and allowance of the application are requested.

Respectfully submitted,

Richard L. Mayer (Reg. No. 22,490)

No. 47084

KENYON & KENYON One Broadway

New York, New York 10004 (212) 425-7200 (telephone)

(212) 425-5288 (facsimile)

CUSTOMER NO. 26646

Dated:\\)00. 14, 7.004

[2345/208]

CONTENT AND SECURITY PROXY IN A MOBILE COMMUNICATIONS SYSTEM

FIELD OF THE INVENTION

The present invention relates to a method and a device for making available security functions during the transmission of data from or to a subscriber terminal unit of a mobile communications network.

BACKGROUND INFORMATION

Current and new data services offer subscribers of mobile communications networks direct access to the Internet_internet and other public data networks. Therefore, the mobile telephone used for mobile application, and ancillary equipment driven by it, such as a notebook or a personal digital assistant, are at the mercy of the most varied attacks by third parties, similar to what happens in a fixed networkbased Internet access.

SUMMARY OF THE INVENTION

state_concern a method and a device for making available
security functions in the transmission of data from and to a
subscriber terminal unit of a mobile communications network,
so as to effectively protect the subscriber terminal unit and
units connected to it or combined with it.

This object is attained by the features of the independent elaims. The cruxEmbodiments of the present invention is, concern, in a cellular mobile telephony network, to offer a security service that is able to be personalized, individually per cellular mobile telephony connection and subscriber.

The In embodiments of the present invention, the subscriber may adjust his security settings interactively or dynamically.

The network operator may specify a series of meaningful standard settings for the filter functions, such as virus protection, protection from advertising mail, etc.

In this context, the protective function is offered by a network-specific device in the form of a security and filtering device. In addition, the general protective function may be coupled with a memory function, i.e., parts of the data traffic are temporarily stored in the device, and may be retrieved by the subscriber. Consequently, the security and filtering device may additionally take over the function of a so-called proxy. Proxy Proxy means as much as prepresentative service. Proxies accept requests from a client, for instance, a terminal unit, and pass them on, possibly modified, to the original destination, such as an Internet internet supplier. Proxies are able locally to file data that are passed through and to deliver them upon the next access.

With that, at the same time, one achieves can achieve an increased performance, since certain contents may be buffered.

According to the present invention, the following protective functions may be offered by the system embodiments described:

_Filtering of the data traffic on an IP/TCP basis in the form of a so-called firewall <u>function;</u>

function. Furthermore, filtering/refusing_Filtering/refusing data packets of a certain origin (IP address) or data packets from and to certain services (TCP ports); and

_An analysis of the data content for contents that are malicious or critical to security.

The entire content of a data connection is analyzed and searched according to certain patterns. Signatures of viruses, etc, are tracked down and rendered harmless before they reach the terminal unit of the subscriber.

An analysis of the data content for undesired subject matter, such as in the form of spam, advertising or offensive material. For this, the entire content of the connection is analyzed and content stated by the subscriber as being undesired is filtered out, for instance, to protect children and juveniles.

The network operator himself is able to use the mechanisms of the system in order purposefully to cut out, for certain subscribers, certain data traffic, such as services liable to costs, if the subscriber has not subscribed to this service.

The filtering function for the data content may be enhanced meaningfully and technically, using the same mechanisms additionally using the following functions.

For example, a limiting of the data transfer volume <u>iscan be</u> relatively easy to implement. To do this, the entire traffic, under certain circumstances separated into incoming and outgoing traffic, is summed up, and additional traffic is stopped if the limit specified by the user or operator is exceeded.

In addition, budget compliance may be checked, using one component to calculate the compensation. The subscriber or the

operator may specify a certain upper limit for communications cost. If the established budget is exceeded, the subscriber is notified and the data traffic is stopped. This makes possible an effective cost control and cost transparency.

Additional functions may be integrated into the system in a meaningful way: way as indicated in the following.

If certain events occur, i.e., if attacks are detected, spam mails are filtered or similar events are recognized by the system, and notification is made of the subscriber or network operator, in order to enable a transparent control of the data filtered out.

The subscriber may also decide administratively whether histhe subscriber/s entire traffic should be conducted over the system or only selectively, i.e., at certain times, according to specific incidents or upon suspicion of misuse.

According to one refinement In embodiments of the present invention, a distributed implementation of the filter functions may be provided, i.e. the security and filter device is not provided centrally in one network node of the mobile communications system, but rather in a distributed manner, or individually in a plurality of network nodes. The load on a single node is reduced thereby.

This device of the system may

- a) be conditioned spatially or upon network technology,
 i.e. distribution to several networks or network nodes,
- b) be conditioned functionally, for instance, special filter components for certain data contents, and, for example, email filters, virus filters, etc., or

c) conditioned upon architecture or software technology, based, for example, on the use of special hardware and system software for certain functions.

The administration of these additional functions may be performed in each case centrally, from a certain node.

An exemplary embodiment of the present invention is explained below, in the light of a drawing.

BRIEF DESCRIPTION OF THE DRAWING

Figure 1 schematically shows shows a schematic of the technical design of the system.

DETAILED DESCRIPTION

The system is a part of a mobile communications network 10, which premitspermits a multiplicity of subscriber terminal units 13 communications with other public networks, such as the Internet_internet_11. Furthermore, combined units 14, such as PC, PDA, <a href="a personal computer (PC), personal digital <a href="assistant (PDA), Smartphone, etc., <a href="that are connected to cellular mobile telephony terminal unit 13, may be provided, which make possible a comfortable, mobile Internet Internet Internet</a

Security and filter device 1 is situated within mobile communications network 10, preferablye.g., within an appropriate network node, such as an exchange MSC, and according to the present invention, it may be made up of the following functional parts described below.

General filter component 2:

This component has a variable filtering function specifiable by the subscriber/network operator, and itoperator. It

analyzes in real time the data flow 12 exchanged between terminal unit 13 of the subscriber and Internet internet 11. Subscriber traffic 12 in both directions goes via this filter 2 and is analyzed there.

Authentication component 3:

In order to use security and filtering device 1, the subscriber has to authenticate himself vis-a-vis the system. Thereby Thus, it is ensured that no unauthorized access can take place to, for instance, example, the personal settings of the subscriber. In the simplest case, For example, the authentication may occur via call number MSISDN of the subscriber. The subscriber is protected more securely and better by the use of an additional PIN or a password. If necessary, a cryptographic authentication method may be used, e.g., certificates of the subscriber.

Administrative component 4:

This component forms the interface between the system and the subscriber. Here the subscriber may administer his the subscriber's personal settings. This can be done directly via the cellular mobile telephony system, the <a href="https://www.nister.

Database 5:

Database 5 describes which data are to be filtered out by filtering component 2 or are to be processed. This database 5 mayadvantageously be split up into four databanks. First databank 6 <u>includesmay include</u> the individual filter and settings per subscriber. Second databank 7 <u>includesmay include</u> the filter and settings per mobile phone type.

Third databank 8 <u>includesmay include</u> the network operator-specific settings and filter, and fourth databank 9 <u>includesmay include</u> the general settings and filter.

What is Claimed is:

WHAT IS CLAIMED IS:

Abstract ABSTRACT OF THE DISCLOSURE

The invention relates to and method and device for providing is provided for making available security functions during the transmission of data from and to a subscriber terminal of a mobile communications network. A real-time analysis of the data flow from and to the subscriber terminal is carried out in a device of a network node of the mobile communications network during which data with contents defined beforehand by the subscriber or by a network operator / provider are identified and processed. This results in protecting the terminal and subscriber's devices connected thereto from external attacks—in the best way possible.